

Slate Effect Flooring Tiles Spec-Sheet

CHARACTERISTICS	STANDARDS	MEASUREMENT UNIT	REQUIREMENTS	AVERAGE VALUES
Hardness	ISO 7619	Shore A	≥ 75	85 ± 5
Abrasion resistance	ISO 4649	mm ³	≤ 250	140
Dimensional stability	EN 434	%	± 0.4 max	≤ 0.4
Electrical resistance	IEC 60093	Ohm		$> 10^{10}$
Resistance to stains	EN 423			Resistant
Acoustic insulation when walked upon	ISO 140 - 8	dB		10
Colour fastness to artificial light	ISO 105-B02 Met. 3	degree	≥ 6 Blue \geq grey scale	In accordance
Fire behavior	DIN 4102 UNI 8457 – UNI9174 NEP 92-507	Class	B1 1 M3	B1 1 M3
Effect of a castor chair	EN 425 castor wheels type W		No alterations	Suitable
Residual indentation	EN 433	mm	≤ 0.25	0.1
Thermal resistance	DIN 52612	M ² K/W		0.022
Electrostatic charge when walked upon	EN 1815	kV	≤ 2	≤ 2 (antistatic)
Slipping resistance	DIN 51130 BCRA TORTUS TEST	Class μ	BIA ≥ 0.40	R9 ≥ 0.50
Cigarette burns	EN 1399	rating	Metodo A ≥ 4 Metodo ≥ 3	In accordance
Flexibility	EN 435 Met.A ($\Phi 20$ mm)		No fissuring	No fissuring