

RUBBER FLOORINGS - INSTRUCTIONS FOR USE

Important: These instructions must be used in conjunction with our flooring guide. Ask for and consult the installation and maintenance manuals. A copy is also available on our web-site at <http://polymax.co.uk/Material-Info/Rubber-Flooring-Installation-Guide.pdf>

- Rubber floorings are designed for indoor applications.
- Only the black-coloured can be installed outdoor.
- Do not bend the flooring.
- Do not expose to direct sunlight.
- Automobile tires can leave indelible marks on the flooring.
- Black floorings can leave halos on objects with which they come in contact.
- Check the type, quantity, colour and lot number indicated on the packaging. Any defect or difference with respect to what was ordered or any other claim must be notified in writing within 7 days from the date of receipt of the material.
- Let the material acclimatize at the installation site for least 48 hours before laying it. After this remove the rubber flooring from its packaging and lay the rolls down without cutting and/or adhesive at least 12 hours prior to installation. (You may need to re-roll the rubber flooring in the opposite direction and put weights on the ends if they are curling up during this time)
- Slight colour shade differences may be found among different production lots of the same colour.
- **If you are un-happy with any aspects of the flooring at this stage, please contact our sales team on 01420 474123 before trimming and/or putting the adhesive as no claims are accepted for floorings that already been cut or laid.**
- Do not use adhesives on sub-flooring with residual humidity greater than 75% (as per BS 8203 standard).
- The temperature at the installation site must not be lower than 15 degrees.
- Once laid proceed to clean and to wax the floorings that have already been laid.
- **Failure to comply with instructions or to consult the installation and maintenance manuals invalidates any claims.**