

SPECIFICATION

規格・СПЕЦИФИКАЦИЯ・ESPECIFICACIÓN


 2.0mm
2.5mm

 2.0mm: 2m x 20m = 40m²
2.5mm: 2m x 20m = 40m²

 2.0mm: 2430g/m²
2.5mm: 3100g/m²

GENERAL PERFORMANCE

EN 13845

ASTM F1303

Agrément - G5ws


REACTION TO FIRE

 EN 13501-1 Class Bfl-S1 { EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass

ASTM E648 Class 1*


ENHANCED SLIP

Sustainable wet slip resistance*

AS/NZS 4586 R10

EN 13845 ES1

RRL Pendulum Test ≥36 (wet test - 4S Rubber/Slider 96)

Surface roughness Rz ≥20µm

The slip resistance across all Venue products is assured throughout the guaranteed life of the product, with strict adherence to HSE Guidelines.


ABRASION RESISTANCE

EN 13845 50,000 cycles

EN 649 Group T


VOC EMISSIONS

AqBB VOC test : Pass

(Low Result)


AGRÉMENT ASSURANCE

Venue Standard has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance, colour and slip resistance will be retained during this period.


HYGIENE

Contains antimicrobial agents. This product has been independently tested and results demonstrate that it inhibits the growth of MRSA on the flooring. An effective cleaning regime is however, the most important defence against infection.


ELECTRICAL BEHAVIOUR

(body voltage)

EN 1815 ≤2kV

Classified as 'antistatic'


RESISTANCE TO CHEMICALS

Good resistance to dilute acids and alkalis. Chemical resistance charts available on request.


APPLICATIONS

Venue Standard is ideal for use in areas where contaminant spillages can occur, making slip resistance an important consideration. Typical areas include clinics, laundry and sluice rooms, nursing homes, washrooms, WCs, bar serveries, food preparation areas, kitchens, canteens and institutional applications. For continually wet areas please refer to our Venue Hydro range. As with all Venue products, Venue Standard should not have a polish applied.

SAFETY FLOORING

Heavy-duty safety flooring

 英伦经典装饰效果,
超耐用安全防护地板

 Износостойкое антискользящее
напольное покрытие

Pavimento vinílico antideslizante


 Decoration and shade may vary slightly from the samples shown.
The data presented is correct at the time of printing.

实际产品与样卡的色调和图案可能有轻微变

 Дизайн и оттенок материалов могут слегка отличаться от представленных образцов.
Данные информации являются верной на момент публикации. Пожалуйста,
обратиться к нашему сайту www.polyfor.com для получения последних новостей.

 El diseño y la tonalidad pueden variar levemente de las muestras obtenidas.
Los datos presentados eran correctos en el momento de su impresión.