

## **Polymax EPDM Cord**

When your application requires the rubber to withstand atmospheric conditions; ozone, sunlight UV ageing, moisture, Polymax EPDM Rubber Cord is most suitable

### **Technical Properties (Summary)**

<i>Material:</i>	EPDM
<i>Colour:</i>	Black
<i>Density (specific gravity):</i>	1.5g/cm <sup>3</sup>
<i>Shore Hardness:</i>	70 ± 5 Shore A
<i>Tensile Strength</i>	14 N/mm <sup>2</sup> .
<i>Elongation at Break:</i>	300%
<i>Min. Temperature:</i>	-30°C
<i>Max. Temperature:</i>	+150°C
<i>Compression set:</i>	16%

### **Size:**

For details on custom size strip / gasket with self adhesive backing please call.

<b>Thickness(mm)</b>	<b>Width(mm)</b>	<b>Length(mm)</b>	<b>Colour</b>
1-25	-	-	<b>Black</b>

NB: The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any particular application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable, but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied.