

Safety Data Sheet

LATEXPLAN TRADE comp. A

Safety Data Sheet dated 27/11/2012, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier
Trade name: LATEXPLAN TRADE comp. A
- 1.2. Relevant identified uses of the substance or mixture and uses advised against
Cement based levelling mortar.
Uses advised against: ==
- 1.3. Details of the supplier of the safety data sheet
Supplier:
MAPEI U.K. Ltd - Mapei House Steel Park Road
Halesowen - West Midlands B62 8HD
Competent person responsible for the safety data sheet:
sicurezza@mapei.it
- 1.4. Emergency telephone number
MAPEI U.K. Ltd - phone: +44(0)121 508 6970
fax: +44(0)121 5086 960
www.mapei.co.uk (office hours)

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
Directive criteria, 67/548/CE, 1999/45/EC and following amendments thereof:
Properties / Symbols:
 Xi Irritant
- R Phrases:
R41 Risk of serious damage to eyes.
R43 May cause sensitization by skin contact.
- Adverse physicochemical, human health and environmental effects:
No other hazards
- 2.2. Label elements
- 
- Xi
- Symbols:
 Xi Irritant
- R Phrases:
R41 Risk of serious damage to eyes.
R43 May cause sensitization by skin contact.
- S Phrases:
S22 Do not breathe dust.
S24/25 Avoid contact with skin and eyes.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- Contents:
Portland cement, Cr(VI) < 2 ppm

Safety Data Sheet

LATEXPLAN TRADE comp. A

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

See at paragraph 11 the additional information concerning crystalline silica

This preparation contains cement. Contact between cement and body fluids (e.g. sweat and eye fluids) may cause irritation or burns.

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and corresponding classification:

25% - 50% free crystalline silica ($\text{Ø} > 10 \mu$)

CAS: 14808-60-7, EC: 238-878-4

10% - 20% Portland cement, Cr(VI) < 2 ppm

CAS: 65997-15-1

Xi; R37/38-41-43

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Wash the mouth thoroughly and drink plenty of water. In case of disease consult a physician immediately and present this safety-data sheet.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

If brought into contact with the eyes, the product causes serious eye injury, such as opacity of the cornea or lesions to the iris.

If brought into contact with the skin, the product may cause sensitisation of the skin.

This preparation contains cement. Contact between cement and body fluids (e.g. sweat and eye fluids) may cause irritation or burns.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Safety Data Sheet

LATEXPLAN TRADE comp. A

Treatment:
(see paragraph 4.1)

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
 - Suitable extinguishing media:
Carbon dioxide (CO₂).
 - Extinguishing media which must not be used for safety reasons:
None in particular.
- 5.2. Special hazards arising from the substance or mixture
 - The product does not present a fire hazard
- 5.3. Advice for firefighters
 - Use suitable breathing apparatus .
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
 - Wear personal protection equipment.
 - Remove persons to safety.
 - See protective measures under point 7 and 8.
- 6.2. Environmental precautions
 - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- 6.3. Methods and material for containment and cleaning up
 - Rapidly recover the product, wearing protective clothing.
 - Scoop into containers and seal for disposal.
 - After the product has been recovered, rinse the area and materials involved with water.
- 6.4. Reference to other sections
 - See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
 - Avoid contact with skin and eyes and exposure to high dust concentration.
 - Avoid powder development and deposit
 - Contaminated clothing should be changed before entering eating areas.
 - Do not eat or drink while working.
 - See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
 - Always keep the containers tightly closed.
 - Incompatible materials:
Keep away from water or from damp surroundings.
 - Instructions as regards storage premises:
Adequately ventilated premises.
- 7.3. Specific end use(s)
 - None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
 - free crystalline silica ($\text{Ø} > 10 \mu$) - CAS: 14808-60-7
TLV TWA: - 0,05 mg/m³ (respirable fraction)
 - Portland cement, Cr(VI) < 2 ppm - CAS: 65997-15-1

Safety Data Sheet

LATEXPLAN TRADE comp. A

TLV TWA: - (polvere)10 mg/m³

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Safety goggles.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Not needed for normal use.

A dust mask (P2) should be worn if above exposure limits

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Thermal Hazards:

None

Environmental exposure controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	powder
Colour:	grey
Odour:	slight, typical of cement
Odour threshold:	N.A.
pH:	N.A.
pH(water dispersion, 10%):	12
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	== °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	== °C
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	N.A.
Apparent density:	1,95-2,05 g/cm ³
Vapour density (air=1):	N.A.
Solubility in water:	partly soluble
Solubility in oil:	insoluble
Viscosity:	N.A.
Auto-ignition temperature:	== °C
Explosion limits(by volume):	==
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Explosive properties:	==

Safety Data Sheet

LATEXPLAN TRADE comp. A

Oxidizing properties:	N.A.
9.2. Other information	
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Route(s) of entry:

Ingestion: Yes

Inhalation: Yes

Contact: No

Toxicological information related to the product:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

N.A.

Corrosive/Irritating Properties:

Skin:

The product can cause irritation by contact.

Eye:

The product can cause damage to eyes by contact

Sensitizing Properties:

Frequent and prolonged skin contacts with cement paste may cause dermatitis.

Carcinogenic Effects:

The IARC (International Agency for Research on Cancer) believes that the crystalline silica inhaled at the workplace can cause lung cancer in man.

However, it also points out that the cancer effect depends on the silica characteristics and on the biological-physical condition of the environment.

There is a large amount of information in support of the fact that increased risk of cancer is limited to persons suffering from silicosis.

In the current situation of studies, protection of workers from silicosis can be ensured by respecting the exposure limit values.

Mutagenic Effects:

Safety Data Sheet

LATEXPLAN TRADE comp. A

No effects are known.

Teratogenic Effects:

No effects are known.

Additional Information:

Susceptibility to skin irritation and sensitization varies from person to person.

In a sensitized individual the allergic dermatitis may not appear until after several days or weeks of frequent and prolonged contact.

Therefore, even though the skin irritation potential is slight, skin contact should be avoided. Once sensitization has occurred, exposure of the skin to very small quantities of the material may cause erythema and edema.

For this reason, the contact with the skin should be avoided. Once sensitization has occurred, exposures to small amounts of material may cause erythema and edema locally.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Not available data on the mixture

Adopt good industrial practices, so that the product is not released into the environment.

N.A.

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

Not available data on the mixture

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

Disposal of hardened product (EC waste code) : 17 01 01

Disposal of not hardened product (EC waste code) : 17 01 01

The suggested European waste code is just based on the composition of the product.

According to the specific process or application field a different waste code may be necessary.

SECTION 14: Transport information

902373-UK/1

Page n. 6 of 9

Safety Data Sheet

LATEXPLAN TRADE comp. A

- 14.1. UN number
UN Number: ==
- 14.2. UN proper shipping name
N.A.
- 14.3. Transport hazard class(es)
Rail/Road(RID/ADR): no dangerous good
ADR-Upper number: NA
Air (ICAO/IATA): no dangerous good
Sea (IMO/IMDG): no dangerous good
N.A.
- 14.4. Packing group
N.A.
- 14.5. Environmental hazards
ADR Environmental Pollutant:
Marine pollutant: No
N.A.
- 14.6. Special precautions for user
N.A.
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
No

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)
Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Dir. 2006/8/EC
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP)
Regulation (EU) n. 453/2010 (Annex I)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

REACH Regulation (1907/2006)

REACH Regulation (1907/2006) – All. XVII

The product contains Cr (VI) under the limitse established by annex. XVII pt.47. Respect the duration according to the information described on the packaging

REACH Regulatio n° 1907/2006 (REACH) – Art. 59 (Substances in “Candidate List”): N.A.

CLP Regulation n° 1272/2008 (CLP) and s.m.i.

Directive n° 1999/45/CE (Dangerous Preparation) and s.m.i.

Directive n° 67/548/CEE (Substances) and s.m.i.

Directive 2000/39/CE and s.m.i. (Professional threshold limit)

Directive 105/2003/CE (Seveso III): N.A.

ADR Agreement – IMDG Code – IATA Regulation

Wassergefährdungsklasse:

VOC (2004/42/EC) : N.A. g/l

Safety Data Sheet

LATEXPLAN TRADE comp. A

Social Dialogue on Respirable Crystalline Silica

On April 26, 2006 was signed a multi-sector social dialogue, based on a "Guide to Good Practices", on workers health protection who are in contact with products containing crystalline silica. The text of the agreement published in G.U. European Union (2006 / C 279/02) and the "Guide to Good Practices", with attachments, are available on www.nepsi.eu website, they offer guidelines and useful information for handling products containing respirable crystalline silica.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitization by skin contact.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

Safety Data Sheet

LATEXPLAN TRADE comp. A

IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL:	European threshold limit value
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
N.A.:	N.A.
N.D.:	