


Unit 75, Whitehill & Bordon Enterprise Park Budds Lane, Bordon, Hampshire GU35 0FJ

Email: sales@polymax.co.uk Tel: +44 (0)1420 474 123



Oval Buffer Extended 65L x 33W x 52H

Product SKU: 6006402

Two bolt hole rubber bump stops suitable for use on lorries, vans, ramps, loading bays and doors.

The oval rubber bumper stop can be easily fitted to almost any surface via the counter sunk holes. These buffers are made from hardwearing UV resistant SBR rubber and are available as hollow cored or a non-hollow cored version. There are 3 versions of this buffer: The solid buffer for heavy impact, a hollow cored version to suit lighter applications and the extended base version which gives 52mm of clearance.

Colour: Black

Material: NR/SBR

Operating temperature range: -15°C to 70°C

Physical Property	Unit	Typical Values
Hardness	ShA	75
Elongation at Break	%	200
Tensile Strength	MPa	4
Weight	KG	0.09

Although the technical details and recommendations made correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use Polymax products must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product. All sales subject to our standard terms www.polymax.co.uk/sales-terms